

IS 5784 : 2001

(Reaffirmed 2014)

(Reaffirmed 2016)

(Reaffirmed 2019)

भारतीय मानक
शेविंग साबुन — विशिष्टि
(पहला पुनरीक्षण)

Indian Standard
SHAVING SOAP — SPECIFICATION
(*First Revision*)

ICS 71.100.40

© BIS 2001

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

September 2001

Price Group 3

Soaps and Other Surface Active Agents Sectional Committee, CHD 25

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Soaps And Other Surface Active Agents Sectional Committee had been approved by the Chemical Division Council.

This standard was originally published in 1970. Based on the experience gained over the years, the technical committee responsible for formulation of this standard decided to revise it. In the present (first revision), a new requirement of potassium content in total alkali has been incorporated alongwith its test method.

Shaving soaps are designed to soften the beard which is a necessary prerequisite for a smooth and clean shave. They may be manufactured by the cold or semi-boiled or full boiled process where high grade oils, fats, fatty acids, etc, are saponified with a mixture of caustic potash and caustic soda.

A scheme for labelling environment friendly products known as ECO-Mark has been introduced at the instance of the Ministry of Environment and Forests (MEF), Government of India. The ECO-Mark would be administered by the Bureau of Indian Standards (BIS) under the *Bureau of Indian Standards Act*, 1986 as per the Resolutions No. 71 dated 21 February 1991 published in the Gazette of the Government of India. For a product to be eligible for marking with ECO logo, it shall also carry the ISI Mark of BIS besides meeting additional environment friendly requirements. The requirements to be satisfied for a product to qualify for the BIS Standard Mark for ECO friendliness, has been included in this revision. These requirements will be optional; manufacturing units will be free to opt for the ISI mark alone also.

There is no ISO specification on this subject. This standard is formulated based on indigenous technology and data available.

Composition of the Committee responsible for formulating this standard is given in Annex B.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

IS 5784 : 2001

Indian Standard

SHAVING SOAP — SPECIFICATION

(First Revision)

1 SCOPE

This standard prescribes the requirements and method of sampling and test for shaving soap.

2 REFERENCES

The following standards contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below:

IS No.	Title
286 : 1978	Methods of sampling and test for soaps (<i>second revision</i>)
1070 : 1992	Reagent grade water (<i>third revision</i>)
4955 : 1993	Household laundry detergent powder (<i>third revision</i>)
13424 : 1992	Safety evaluation of bathing bar and toilet soap — Methods of test

3 REQUIREMENTS

3.1 Description

Shaving soap shall be of high grade, thoroughly saponified soap, milled and plodded, white or coloured, and perfumed, and compressed to firm smooth cakes in the form of cup soaps or sticks. They shall produce profuse, stable and creamy lather.

3.2 Ingredients

In addition to perfume and moisture, shaving soaps may contain colouring matter, preservatives, medicaments and super fatting agents and such additional substances as are declared on the label. All these materials shall be non-injurious in use with soap.

3.3 Shaving soaps shall also comply with the requirements specified in Table 1.

3.4 Additional Requirements for ECO-Mark

3.4.1 General Requirements

3.4.1.1 The product shall conform to the requirements for quality, safety and performance prescribed under 3.1 to 3.3.

Table 1 Requirements For Shaving Soap
(Clause 3.3)

Sl No.	Characteristic	Require-ment	Method of Test, Ref to	
			Clause No. in IS 286	Annex of this Standard
(1)	(2)	(3)	(4)	(5)
i)	Moisture and volatile matter, percent by mass, <i>Max</i>	12.0	4	—
ii)	Matter insoluble in alcohol, percent by mass, <i>Max</i>	2.0	5	—
iii)	Free caustic alkali (as KOH), percent by mass, <i>Max</i>	0.01	6	—
iv)	Chlorides (as KCl), percent by mass, <i>Max</i>	1.5	10	—
v)	Unsaponified fatty matter, percent by mass, <i>Max</i>	0.5	13	—
vi)	Rosin acids, percent by mass, <i>Max</i>	Nil	14	—
vii)	Total fatty matter, percent by mass <i>Min</i>	74.0	15	—
viii)	Titre of total fatty acids, °C, <i>Min</i>	45	16	—
ix)	Glycerol, percent by mass, <i>Min</i>	2.0	22	—
x)	Free carbonate alkali, percent by mass, <i>Max</i>	0.5	28	—
xi)	Potassium content, (as K ₂ O) in total alkali, percent by mass, <i>Min</i>	50.0	—	A

3.4.1.2 The manufacturers shall produce to BIS environmental consent clearance from the concerned State and Pollution Control Board as per the provisions of the *Water (Prevention and Control of Pollution) Act*, 1974 along with the authorization, if required under the *Environment (Protection) Act* 1986, while applying for ECO-Mark.

3.4.2 Specific Requirements

3.4.2.1 The material shall neither contain any synthetic detergent when tested as per the method given in Annex B and C of IS 4955 nor any phosphate when tested as per the method prescribed in 20 of IS 286.

3.4.2.2 The material shall pass the test for dermatological safety when evaluated as per the method prescribed in IS 13424.

4 SAMPLING

Sampling and criteria for conformity material shall be as prescribed in 3 of IS 286.

IS 5784 : 2001

5 PACKING AND MARKING

5.1 Packing

The material shall be packed as agreed to between the purchaser and the supplier.

5.1.1 For ECO-Mark the product shall be packed in such packages which are made from recyclable/reusable or biodegradable material and declared by the manufacturer and may be accompanied with detailed instructions for proper use.

5.2 Marking

The packages shall be securely closed and clearly marked with the following:

- a) Name of the material;
- b) Indication of source of manufacture;
- c) Recognized trade-mark;
- d) Year of manufacture;

- e) Batch No./Control unit No; and
- f) Following critical ingredients mentioning the actual compound in descending order up to a limit of 0.5 percent by mass, except moisture:
 - 1) Total fatty matter (TFM), and
 - 2) Matter insoluble in alcohol.

5.2.1 Each package may also be marked with the Standard Mark.

5.2.2 Additional Marking for Eco-Mark

The criteria for which the product has been labelled as ECO-Mark.

6 QUALITY OF REAGENTS

Unless specified otherwise, pure chemicals and distilled water (see IS 1070) shall be employed in the tests.

NOTE — 'Pure chemicals' shall mean chemicals that do not contain impurities which affect the results of analysis.

ANNEX A

[(Table 1, Sl No. (xi)]

DETERMINATION OF POTASSIUM IN SHAVING SOAP

A-1 GENERAL

Two methods, namely, gravimetric and flame photometric methods have been prescribed for determination of K_2O .

A-2 METHOD 1 (GRAVIMETRIC METHOD)

A-2.1 Apparatus

A-2.1.1 Muffle Furnace

A-2.1.2 Platinum Crucible

A-2.1.3 Sintered Glass Crucible (Porosity No. 4)

A-2.1.4 Air Oven

A-2.1.5 Desiccators

A-2.2 Reagents

A-2.2.1 Hydrochloric Acid — 0.1 N and 2 N.

A-2.2.2 Sodium Tetraphenylboron Solution

Dissolve 3.0 g of the solid reagent in 500 ml of distilled water in a glass-stoppered bottle. If the solution is turbid add about 1 g moist aluminium hydroxide gel, break up the gel if necessary, and shake the suspension

for 15 min. Filter through a Whatman No. 40 filter paper. Refilter the first part of filtrate, if necessary, to ensure a clear filtrate.

A-2.2.3 Wash Solution

Precipitate about 0.1 g potassium (present as potassium chloride in 50 ml water) with 40 ml of sodium tetraphenylboron solution added slowly and with constant stirring. Allow to stand for 30 minutes, filter through a sintered glass filtering crucible. Wash with distilled water, and dry for one hour at 120°C. Shake 20-25 mg of the dry precipitate with 200 ml distilled water in a stoppered bottle at 5 minutes intervals during one hour. Filter through a Whatman No. 40 filter paper and use the filtrate as wash-liquid.

A-2.3 Procedure

A-2.3.1 Weigh accurately 0.5 to 1.0 g of soap sample in a platinum crucible. Ash in a muffle furnace at 800°C. Extract the residue with 2 N HCl and dilute to 100 ml in a standard volumetric flask. Mix well. This is sample solution.

A-2.3.2 Transfer 50 ml of solution into a 250-ml beaker. Introduce from a burette 40 ml of the sodium

IS 5784 : 2001

tetraphenylboron reagent slowly taking 5-10 minutes and stir continuously. The temperature throughout must be kept below 20°C. Allow the precipitate to settle during one hour. Collect the precipitate on a sintered glass filtering crucible (porosity No. 4), wash the precipitate with a small volume (5-10 ml in small portion) of wash solution (see A-2.2.3) and finally with 1-2 ml of ice-cold distilled water. Dry at 120°C and cool the covered crucible in a desiccator.

A-2.4 Calculation

$$\text{Potassium (as K}_2\text{O), percent by mass in total alkali} = \frac{26.32 M_1 \times 100}{M_2 \times 12.36}$$

where

M_1 = mass in g of the precipitate, and

M_2 = mass in g of soap sample.

A-3 METHOD 2 (FLAME PHOTOMETRIC METHOD)

A-3.1 Apparatus

A-3.1.1 Flame Photometer

Use a flame photometer equipped with atomizer, burner, optical selective device consisting of the reflectors, lenses interference filters and diaphragms; and measuring instrument consisting of photocell, amplifier and sensitive galvanometer. The galvanometer scale ranges from 0 to 100 divisions, which measures the intensity of the radiation, transmitted by the element.

A-3.2 Reagents

A-3.2.1 Standard Potassium Solution

Weigh exactly 1.582 g of potassium chloride, dissolve in water and dilute to one litre with water in measuring flask. This solution contains 0.1 g K_2O per 100 ml.

A-3.2.2 Calibration Graph

Take 10, 20, 40, 60 and 80 ml of standard potassium solution (see A-3.2.1) and dilute to 100 ml with distilled water in different measuring flasks. Each flask now contains 0.01, 0.02, 0.04, 0.06 and 0.08 g K_2O per

100 ml. Use these dilute solutions to obtain a corresponding galvanometer reading as given in A-3.3 and plot the concentration against galvanometer reading in a rectangular co-ordination graph. Draw a smooth curve over the points, which gives a calibration graph in the graph in the range 0.01 to 0.1 percent K_2O .

A-3.3 Procedure

A-3.3.1 Sample Solution

Prepare the sample solution as in A-2.3.1.

A-3.3.2 Insert the potassium filter corresponding to wavelength 767 nm light burner fed by illuminating gas (laboratory gas) and adjust the specified air pressure between 0.5 to 0.7 kg/cm² and maintain the control knob. First spray water and adjust the pointer to zero in galvanometer scale by zero adjustment knob. Then spray the standard potassium solution (see A-3.2.1) and adjust the deflection to maximum (100) by using sensitivity control knob. Again spray water to see pointer comes to zero; then spray standard solution to indicate 100. Repeat till water reads zero and standard solution reads 100 with same adjustment during both the operations. Now reading zero by water and with the same adjustment 100 by standard solution indicate that the instrument is ready for measurement.

A-3.3.3 Without altering the earlier adjustment of the instrument, spray various diluted solutions prepared in A-3.3.2 and obtain a calibration graph in the range 0.01 to 0.1 percent K_2O . After washing with water, spray the sample solution and obtain the galvanometer reading. From the graph, read out the corresponding concentration of K_2O in the solution (say A).

A-3.4 Calculation

$$\text{Potassium (as K}_2\text{O), percent by mass in total alkali} = \frac{A \times 10^4}{M \times 12.36}$$

where

A = concentration of K_2O in the sample solution from the calibration curve, and

M = mass of soap sample taken for preparing the sample solution, in g.

IS 5784 : 2001

ANNEX B

(Foreword)

COMMITTEE COMPOSITION

Soaps and Other Surface Active Agents Sectional Committee, CHD 25

Chairman

DR P. DASGUPTA

Drugs Controller General of India, New Delhi

Members

SHRI. B. R. WADHAWAN (*Alternate to*
Dr P. Dasgupta)

SHRI YOGESH KAMDAR

Dr N. G. WAGLE (*Alternate*)

CHIEF CHEMIST

DY CHIEF CHEMIST (*Alternate*)

Dr S. K. GHOSH

SHRI N. G. WAGLE

SHRIMATI R. TALWANI (*Alternate*)

Dr C. J. SHISHOO

SHRI SANTOSH YELLORE (*Alternate*)

SHRI SHAISH KUMAR

SHRI B. B. SHARMA (*Alternate*)

SHRI J. S. REKHI

SHRI P. JAYAKUMARAN

SHRI M. A. KHAN (*Alternate*)

SHRI SANTOSH KUMAR

SHRI R. C. DOSHI (*Alternate*)

SHRI A. RANGARAJAN

SHRI S. A. PATEL

SHRI MAHENDRA VYAS (*Alternate*)

Dr A. N. BHAT

Dr V. R. DHANUKA (*Alternate*)

SHRI V. P. MENON

Dr K. B. PATIL

SHRI M. P. NAIK (*Alternate*)

SHRI A. A. WARS

SHRI K. S. KRISHNAN

SHRI S. KRISHNAN (*Alternate*)

SHRI M. S. SULTANIA

SHRI S. S. SHUKLA (*Alternate*)

SHRI BHIMRAO BAGALKOTE

SHRIMATI VASUDHA CHACHAD (*Alternate*)

SHRI P. P. KHANNA

SHRI A. C. KHANNA (*Alternate*)

SHRI A. K. CHAKRAVORTY

SHRI P. K. CHAKRABORTY (*Alternate*)

SHRI K. K. PATEL

SHRI M. A. BHATT (*Alternate*)

Dr B. R. GAIKWAD

SHRI P. K. TIWARI (*Alternate*)

Dr ARUN VISHWANATH

SHRIMATI SHWETA PURANDRE (*Alternate*)

REPRESENTATIVE

SHRI A. K. CHOUDHURI

SHRI R. C. DOSHI

SHRI Y. R. DOSHI (*Alternate*)

Representing

Association for Consumer Action on Safety & Health (ACASH), Mumbai

Central Board of Excise & Customs, Ministry of Finance, New Delhi

Central Pollution Control Board, Delhi

Consumer Guidance Society of India (Regd), Mumbai

Consumer Education and Research Centre, Ahmedabad

Department of Industrial Development, Ministry of Industry, New Delhi

Development Commissioner Small Scale Industries, New Delhi

Directorate General of Supplies and Disposals (Insp Wing), New Delhi

Federation of Associations of Small Scale Soap & Detergent Manufacturers of India,
Delhi

Godrej Soaps Ltd, Mumbai

Gujarat Detergent Manufacturers Association, Ahmedabad

Hindustan Lever Limited, Mumbai

Indian Soaps and Toiletries Manufacturers Association, Mumbai
Karnataka Soaps & Detergents Limited, Bangalore

Khadi & Village Industries Commissioner, Mumbai
K.S. Krishnan Associates (P) Limited, New Delhi

Ministry of Defence (DGQA), Kanpur

Mumbai Grahak Panchayat, Mumbai

Nand Kishore Khanna & Sons, Mumbai

National Test House, Kolkata

Nirma Limited, Ahmedabad

Oil Technologists Association of India, Kanpur

Procter & Gamble India Hygiene & Healthcare Limited, Mumbai

Reliance Industries Ltd, Mumbai

Research, Design and Standards Organization (Ministry of Railways), Lucknow
The Non-Power Soap Manufacturers Association, Mumbai

(Continued on page 5)

IS 5784 : 2001

(Continued from page 4)

Members

REPRESENTATIVE
SHRI LAJINDER SINGH,
Director and Head (Chem)

Representing

Tata Chemicals, Pithampur
Director General, BIS (*Ex-officio Member*)

Member-Secretary

SHRIMATI CHITRA GUPTA
Director (Chem), BIS

Soaps Subcommittee, CHD 25:1

Convenor

DR A. N. BHAT

Hindustan Lever Ltd, Mumbai

Members

DR V. R. DHANUKA (*Alternate to*
Dr A. N. Bhat)
SHRI SUNIL AGGARWAL
SHRI VASUDEV RAI (*Alternate*)
DR C. J. SHISHOO
SHRI SANTOSH YELLORE (*Alternate*)
SHRI N. G. WAGLE
SHRIMATI R. TALWANI (*Alternate*)
DR J. S. REKHI
SHRI. Y. S. BHATNAGAR (*Alternate*)
SHRI S. D. VIJAYARAGHAVAN
DR S. K. TALWAR (*Alternate*)
SHRI P. J. NAIR
SHRI M. A. KHAN (*Alternate*)
SHRI SANTOSH KUMAR
SHRI R. C. DOSHI (*Alternate*)
SHRI A. RANGARAJAN
SHRI K. S. KRISHNAN
DR P. N. VISWANATHAN
DR K. B. PATIL
DR B. R. RAMESH (*Alternate*)
SHRI A. A. WARSI
SHRI M. S. SULTANIA
SHRI S. S. SHUKLA (*Alternate*)
SHRI P. P. KHANNA
SHRI A. K. KHANNA (*Alternate*)
SHRI K. K. PATEL
SHRI M. A. BHATT (*Alternate*)
DR R. K. KHANNA
DR A. D. SHITOLE (*Alternate*)
DR ARUN VISHWANATH
SHRIMATI SHWETA PURANDARE (*Alternate*)
REPRESENTATIVE
SHRI R. C. DOSHI
SHRI ASHOK P. SHAH (*Alternate*)
REPRESENTATIVE

Colgate Palmolive (I) Ltd, Mumbai
Consumer Education and Research Centre, Ahmedabad
Consumer Guidance Society of India (Regd), Mumbai
Development Commissioner, SSI, New Delhi
Directorate General of Health Services, New Delhi
Directorate General of Supplies & Disposals, New Delhi
Federation of Associations of Small Scale Soap & Detergent Manufacturers of India,
Delhi
Godrej Soaps Limited, Mumbai
K.S. Krishnan Associates (P) Limited, Noida
Industrial Toxicological Research Centre, Lucknow
Karnataka Soaps & Detergents Limited, Bangalore
Khadi & Village Industries Commission, Mumbai
Ministry of Defence (DGQA), Kanpur
Nand Kishore Khanna & Sons, Mumbai
Nirma Ltd, Ahmedabad
Oil Technologists Association of India, Kanpur
Proctor & Gamble Hygiene & Healthcare India Limited, Mumbai
Gujarat Sabu Utpadak Maha Mandal Ltd, Ahmedabad
The Non-Power Soap Manufactures Association, Mumbai
University Department of Chemical Technology, Mumbai

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc : No. CHD 25 (874).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters :

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110 002
Telephones : 323 01 31, 323 33 75, 323 94 02

Telegrams : Manaksanstha
(Common to all offices)

Regional Offices :

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg
NEW DELHI 110 002

Telephone

{ 323 76 17
323 38 41

Eastern : 1/14 C.I.T. Scheme VII M, V. I. P. Road, Kankurgachi
KOLKATA 700 054

{ 337 84 99, 337 85 61
337 86 26, 337 91 20

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022

{ 60 38 43
60 20 25

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600 113

{ 254 12 16, 254 14 42
254 25 19, 254 13 15

Western : Manakalaya, E9 MIDC, Marol, Andheri (East)
MUMBAI 400 093

{ 832 92 95, 832 78 58
832 78 91, 832 78 92

Branches : AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE.
FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.
LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM.